


Windmill



Fabric Guide



Cutting Instructions (Measurements include allowance for 1/4" seams)


Fabric	Qty to cut	for 6" block	for 12" block
BG	1 square	4 1/4" x 4 1/4"	7 1/4" x 7 1/4"
#1	1 square	4 1/4" x 4 1/4"	7 1/4" x 7 1/4"
#2	1 square	4 1/4" x 4 1/4"	7 1/4" x 7 1/4"
BG	4 rectangles	1 1/2" x 4 1/4"	2 1/2" x 7 1/4"

Be sure to cut squares on the straight grain of the fabric to avoid stretching.
Cut each square diagonally in both directions, yielding 4 triangles of each fabric.



Assembly

Right sides together, match BG fabric triangles with #1 fabric triangles - fabric #1 on top.
Stitch along right side and press seam toward fabric #1. Trim carefully
Repeat to make 4 combination triangles (BG / #1 half of each quarter of the block.)



Right sides together, place a fabric #2 triangle even with the left edge of a BG fabric rectangle.
Stitch. Press seam toward fabric #2 and trim BG fabric carefully to make triangle as shown.
Repeat to make 4 combination triangles (BG / #2 half of each quarter of the block.)



Right sides together, sew above combination triangles together in pairs, stitching along the long edge of the triangle. Press seams toward the fabric #2 triangle. Trim to measure 3 1/2" for 6" block, or 6 1/2" for 12" block.

Sew two quarter-blocks together, "locking" diagonal seams. Repeat with remaining two quarter-blocks. Assemble the two half-blocks, matching points with a pin.
Press and trim to 12 1/2" for 12" block; trim to 6 1/2" for 6" block.